

PEEL AWAY®

PAINT REMOVAL SYSTEM

PEEL AWAY 8

- **Removes up to 12 layers of paint in one application**
- **Safe lead & Asbestos paint removal**
- **No toxic fumes**
- **Less labour intensive**
- **Preserves most substrates**
- **Removes multiple coats of architectural and tough industrial coatings from virtually all surfaces.**

PEEL AWAY is a thick paste that is applied to unwanted paint coatings then covered with the PEEL AWAY Laminated sheets. Simply leave and then PEEL AWAY with the aid of the spatula supplied.

Suitable for use on surfaces such as:

Most internal and external surfaces – Wood, brick, metal, concrete, painted aluminium, stone, plaster, painted fibreglass. Works on some oil, varnish, acrylic and polyurethane coatings. As all situations vary, always perform a Trial Patch Evaluation. *Peel Away 8 **does not** scorch (darken) timber.

Not suitable for use on surfaces such as:

VENEERS, PLYWOODS and COMPOSITION surfaces or for BAKED ENAMELS, some 2 PART EPOXIES and URETHANES. Do not use on unpainted fibreglass.

PEEL AWAY 8

Size	350 G	1 KG	5 KG	15 KG	225 KG
Laminated Paper	¼ sheet	1 sheet	3 sheets	10 sheets	120 sheets
Average Consumption		0.7sqm	3sqm	8-10sqm	100-120sqm

*All sizes include 1x application spatula & comprehensive instruction and safety sheet

Checklist for a complete, successful job:

- Only use PEEL AWAY Laminated paper sheets
- Available water supply, a nylon brush, trowel or spatula supplied.
- Long thick rubber gloves and overalls
- Eye protection goggles, masking tape, scissors or knife
- Plastic drop sheets for protection of surrounding surfaces
- Extra Laminated paper sheets may be required, because paste coverage may go further.

DIRECTIONS FOR USE:

1. Trial Patch – ALWAYS PERFORM A TRIAL PATCH BEFORE EVERY JOB!

Trial patch evaluation should always be completed before undertaking any paint removal project as all paint systems and surfaces vary. 350g Trial pots and 1kg sizes are available for test purposes.

Surface preparation: It is advised to thoroughly dampen the surface with water prior to applying Peel Away. Do not apply Peel Away in extreme cold or heat. Ideal application temperature should be between 15 - 28 degrees Celsius. Cold weather will slow down the stripping process and extreme heat may cause Peel Away to dry out over time.

2. Application

- i) Apply PEEL AWAY 8 using a brush, trowel or spatula. Application rate varies according to age, type and thickness of coatings you are trying to remove.

Note: An application rate of 3-4mm thick is satisfactory in most cases, however, up to 6mm thickness may be required for very uneven surfaces with multiple coatings. Refer to Trial patch success.

- ii) Cover PEEL AWAY paste with the laminated paper sheets, printed side out. Rub gently to remove air pockets as much as possible. Always overlap and seal edges of the laminated paper sheets with masking tape to provide an air-tight seal. **(Only use PEEL AWAY laminated paper sheets).**
- iii) Correct dwell time will be determined by performing a Trial patch evaluation prior to full application. On average 72 hours minimum.

3. Removal and Cleaning

- i) For ease of removal it is recommended to cut the sheet into smaller sections with a knife.
- ii) For each section, slide a spatula behind the laminated sheet and gently lift the paper with paint & paste. If paste is slightly dry when removing due to high temp– mist wet with water and remove.
- iii) For best results, immediately wash each section thoroughly with water, nylon brush and sponge. Superheated water systems are recommended for commercial applications. For any remaining spots of paint not removed, further apply a thin layer of PEEL AWAY 8 for 1 hour without paper, remove and clean. - **PEEL AWAY 8 is NON CAUSTIC and pH NEUTRAL.**



SAFETY DIRECTIONS:

Note: Peel Away 8 is a safely formulated without toxic chemicals and will not burn the skin. **In case of contact with skin or eyes, wash well with water.**

Protective equipment

- i) Wear long rubber gloves taped to sleeves to prevent PEEL AWAY 8 from contacting skin.
- ii) Where prolonged use is anticipated, apply barrier cream to hands and arms. **Wear eye or face protection when stripping paint off ceilings at all times.** Protect any surface not to be stripped with polyethylene /plastic or protection boards and mask edges. Dispose of contaminated waste, solid or liquid form, in compliance with local regulations. Call EPA on 131 555.

FIRST AID

If poisoning occurs, contact a Doctor or the Poison Information Centre on 13 11 26.

If swallowed, do not induce vomiting. Give a glass of water.

If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

If in eyes, hold eyes open, flood with water for at least 15 minutes and see a Doctor.

Disposal

For household and small quantities, the EPA recommends placing containment into thick plastic bags and then disposal through the council garbage collection. For large quantities and all commercial waste disposals refer to strict local EPA guidelines. Refer to Contractor Guide for more details.

Technical: Every care is taken in preparation of this information. Recommendation of technical advice, verbal or trials is given with no responsibility or warranty. Every site condition is different and product testing is essential. Neither responsibility, nor warranty is expressed or implied for the suitability of the material as actual site conditions are all different.

Marketed and licensed to:

BLDCARE AUSTRALIA Pty Ltd ABN 87 003 914 038
Trading as PEEL AWAY AUSTRALIA - ASIA PACIFIC
Unit 43 Homebush Business Village
11-21 Underwood Rd, Homebush NSW 2140
Phone: 02 9746 6733 Fax: 02 9746 5322

Manufactured under licence by:

HAYMES PAINT PTY LTD
Waringa Drive, Wendouree
Industrial Park
BALLARAT VICTORIA 3355
Phone: 1800 033 431